

INSTALLATION INSTRUCTIONS

For your



Congratulations:

You have just purchased one of the finest methods of protecting your home from hurricane force winds and associated flying debris. Force 12tm Protection has been tested and passed the most rigorous testing requirements in the USA. These instructions will provide you with everything you will need to do to deploy the Force 12 prior to a storm to provide you with maximum protection. If you have any questions, contact your Force 12 dealer or call us at 1-888-999-0663. It is highly recommended that you practice deploying your new Force 12 prior to needing it.

STEP 1:

Your Force 12 dealer has already preinstalled all the necessary anchors for you. If your eyebolts are not in place, remove any covers or caps and screw the eyebolts into the appropriate anchors. (See photo 1).

Photo 1



STEP 2:

Take your Force 12 Screen from the bag and lay it out on the ground in front of the area to be protected. Locate the metal snap hooks that are attached to the screen (See Photo 2). This is the top of your screen. The metal hooks are located on the **back and top** of the screen. Using an appropriate size ladder to reach the eyebolts that will hold the top of the screen, attach the snap hooks, one by one, to the matching eyebolts that are located above the area that is being protected (See photo 3). Attach all snap hooks.

Photo 2



Photo 3


Photo 4



STEP 3:

Loop the ground anchor straps through the eyebolts/anchors in the ground (See photo 4). Following the step by step photos 5-8, secure the strap through the buckles located approximately 14” from the bottom of the screen. Tighten down these straps until the screen is taught between the upper and lower attachments.

Face Bar



Front Bill



Photos 5-8 Insert the free end of the ground anchor strap through the underside of the buckle behind the Face bar (see arrow on photo 5). Pull strap up through and loop over face bar and insert into slot in front of face bar. Pull strap tight. To loosen strap, simply pull up on front “bill” to release tension.

If you have only one screen, you are now complete. If you have an area that requires overlapping screens, repeat the above steps for the next screen. **REMEMBER TO OVER LAP THE SECOND SCREEN ON THE FIRST SCREEN BY USING THE LAST FOUR EYEBOLTS (TWO ON TOP, TWO ON BOTTOM) FROM THE FIRST SCREEN AS COMMON ANCHORS FOR THE SECOND SCREEN.**

These instructions and all written literature, photographs or reproductions associated with Force 12 may not be copied, reproduced or altered without the written permission of Home Safety Solutions, Inc., exclusive distributor of Force 12 for The State of Florida and Caribbean Basin. 1-888-999-0663